

PRETERMINATED WALL MOUNT BOXES WITH SUBSCRIBER CABLE

APPLICATIONS

- Telecom/Datacom;
- FTTH;

PRODUCT FACTS

High-quality wall sockets with SC adapters and subscriber cable; PC or APC polishing; customer-specified length; interferometric geometric control.



PRODUCT SPECIFICATIONS

CABLE PARAMETERS	
Fiber Count	1-4
Cable Construction	Single mode round cable
Jacket Material	LSZH compound
Jacket Colour	White
Fiber Type	SM OS2
Outer Diameter	4,5 mm
CONNECTORS PARAMETERS	
Interface, Connector A	SC adapter
Interface, Connector B	-
Compliance, Connector A	IEC 61754-4, TIA/EIA 601-3
Compliance, Connector B	-
Colour, Connector A	Green (APC) /Blue (PC)
Colour, Connector B	-
Colour, Boot Connector A	Green (APC)/Blue (PC)
Colour, Boot Connector B	-
Polish type, Connector A	UPC / APC
Polish type, Connector B	-
Insertion Loss, Connector A, max	<0.3dB @1550nm (According to IEC 61300-3-4, Method B)
Insertion Loss, Connector B, max	-
Return Loss, Connector A, min	> 50 dB @1550 nm for UPC, > 60 dB @1550 for APC (According to IEC 61 300-3-6)
Return Loss, Connector B, min	-
Connector A, quantity	1-4
Connector B, quantity	-
Polarity	-
TEMPERATURE RANGE	
Installation	- 5°C +50 °C
Operation	- 10°C +70 °C
Storage	- 25°C +70 °C

IDENTIFICATION	
	Batch and product number with barcode on packaging label
PACKAGING	
	Each preterminated wall mount boxes with a subscriber cable in a sealed PE package, packages with cords in a cardboard box (on request)